

FMT - Subrack 4U

The FMT 4U Subrack is featured by a high-density design and low insertion loss. It aims at optimizing performance by accommodating up to 12 connector modules. Cable management is quick and smooth because cables are easily secured and organized with cable hangers. Designed with a sliding rear tray to provide expanded cable mounting area.



Data Centers




High Density Environments



Storage Area Networks (SAN)



Communications Rooms



Data Communication Networks

FEATURES

- Easy network differentiation with colored patch cord routing guides in each tray
- Optimized use of bend-Insensitive, Uni-Boot patch cords for maximum density and reliability
- Efficient cable management and built-in labeling chart make MACs fast and smooth
- Strong fiber management system provides slack storage and bend radius protection

STANDARDS

Compliant with the following standards:

- IEEE 802.3ab-2010 - ETL lab verified (up to 100G Ethernet)
- IEEE 802.3ae 10 Gb/sec
- IEEE 802.3ba 40Gb/s and 100 Gb/s
- IEC 60793-2-10:2019, applicable to A1-OM3 and A1-OM4
- ITU-T G.657.A2 for SM
- GR-449-CORE
- TIA-942
- UL94-V-0
- EIA-310
- RoHS

SPECIFICATIONS

Material: Polished Coated Aluminum

Color: RAL9005 - Black

Dimensions:

- Height: 4U
- Width: 19" (ETSI compatible)
- Depth: 240 mm without sliding tray
360mm including sliding tray

Accessories:

- Blank Dummy Panels - FMT-BP
- Protective Panel - MP3558



Protective panel MP3558

BUILD YOUR ORDER

F 4 U 1 2 D - FMT Subrack 4U

F4U12D-PROTECTIVE - Subrack 4U+protective panel front

F4U12D-PR -FMT Subrack 4U+Protective panel rear and front