

# Fiber ODF With Fiber Management

## Description:

Fibernet's Fiber Optic Distribution Frame solution for comfortably Patching & splicing Or Patch only up to distributing 6 x 144 SC fibers with a spacious fiber management for patch-cords.

## Features:

- > In conformance with GR-449-CORE standards.
- > 19", Metal rack , open frame (available also in 21" & 23").
- > Built with 2 side of Vertical fiber management for patch-cords, Recommended with 2 mm patch-cords, bend-control fixtures for safe slack storage, Side-entry cable management.
- > Vertical side duct has rear and side openings for easy cable access
- > Upper duct with Cable drop, Bend-safe fiber drop separates rack cables yet maintains straight duct line.
- > Vertical cable holders for cables attachment.
- > The bottom of the base frame contains a pigtail duct system that is used to carry patch cords from one rack side to the other or from one rack to another in a back-to-back or side-to-side configuration.
- > Adjustable mounting bracket on the upper side of the rack.
- > Materials :AL 5052-H32 [2mm thickness]
- > Color : RAL 9005 or RAL 7035.

## Specifications and Dimensions:

- > Height: 2.2 meters (42U), 2.6 meters (58U), 1.2 meters (22U)\*.
- > Width: 19" without any extra products, 72cm including fiber management.
- > Depth: 41cm.

**Note:** In the 1.2 meters version, only available with one side of fiber management and to be use with Fibernet type HD drawers.



## Accessories:

---

- > Splice & patch drawers: Type HD , Type F.
- > Horizontal cable management.
- > Bridge connection
- > Patch-cords.

## Ordering Information:

---

**FD**F-\_\_ \_ \_

Unit Height	
22	2.2 meters (42U)
26	2.6 meters (58U)
12	1.2 meters (22U)

Color	
B	Black, Ral 9005
G	Gray, Ral 7035

Width	
1	19"
2	21"
3	23"

Example: **FD**F-**22****B**1

[Unit Height = 42U, Color=Black, Ral 9005, Width=19"]