

Fibernet CAT6A IP67 Solution



Description:


Fibernet presents a complete solution for connecting Ethernet links in harsh environments IP67 rated. The solution include patch cords and waterproof Cat 6A RJ45 connectors.

Features:

- > RJ45 connector with a self-stripping IDC contacts system for quick connection.
- > Tool-less connection
- > Suitable for AWG 22 and AWG 24 solid conductors.
- > Color code according to EIA/TIA 568A and B and location of each contact point figures out on a sticker

Specifications and Dimensions:

- > Waterproof gasket made of nitrile
- > Plastic parts made of ABS or Pc UL94V0
- > IDC contacts :Gold plated
- > Interface contacts : with NI+Au 0.2µm protection
- > Plastic parts made of ABS or Pc UL94V0
- > Waterproof gasket made of nitrile
- > Waterproof boxes IP67
- > 4 holes to fixing on the wall
- > Equipped with 4 stainless screw



Cat 6A IP67 Patch cord:



- > IP water immersion and dust protection for harsh environment
- > Wide range of operational temperature for outside installation -40°C/70°C

Specifications and Dimensions:

ELECTRICAL


- > Electrical Insulation Resistance: 500MQ min.@
- > 100V DC
- > Dielectric Withstanding Voltage: 1000V DC. Or AC. Peak Contact to Contact@ 60Hz for 1 minute.

MECHANICAL

- > Insertion / Extraction Life : 750 Cycles Minimum
- > Tensile Strength: > 20N per Wire

PHYSICAL

- > Housing : High-Impact, Flame-Retardant Plastic, UL 94VO
 - > CONT ACT : Phosphor Bronze Alloy Plated With 50 micro-inch of Gold Over 100 micro-inch of Nickel
 - > Shield Shell : Brass Alloy Plated with 50 micro-inch Nickel (FTP only)
- International Protection Code meet IP67



Ordering Information:

FIB-CO

Number of IP67 Keystones
1
2
3
4

FC6A-S-8-xxx-IP- IP PLUG CAT6A xxx METER CABLE

xxx - Cable Length in Meters