

Front Access Fiber Distribution Frame

Description:

Fibernet's Fiber Optic Distribution Frame solution for comfortably Patching & splicing Or Patch only up to distributing up to 12x144 SC fibers with a spacious fiber management for patch-cords. The Distribution frame allow all front access installation.

Features:

- > In conformance with GR-449-CORE standards.
- > Compline with EIA-310 19" standard rack.
- > Metal rack, open frame.
- > Built with spacious of Vertical fiber management for patch-cords, Recommended with 2 mm patch-cords, bend-control fixtures for safe slack storage, Side-entry cable management.
- > The standard vertical high density cable management dimensions are 200x251mm (Width x Depth).
 - Other dimensions: 200x151mm and 300x251mm.
- Vertical side duct has rear and side openings for easy cable access Upper duct with Cable drop, Bend-safe fiber drop separates rack cables yet maintains straight duct line. Vertical cable holders for cables attachment. The bottom of the base frame contains a pigtail duct system that is used to carry patch cords from one rack side to the other or from one rack to another in a back-to-back or side-to-side configuration.
- > Adjustable mounting bracket on the upper side of the rack.
- > Designed to be mounted to the wall or to back-to-back racks
- > Materials :AL 5052-H32 [2mm thickness].
- > Color: RAL 9005.

Specifications and Dimensions:

- > Height: 1.2 meters (22U), 2.2 meters (42U), 2.6 meters (58U).
- > Width: 19" without any extra products, 100cm including fiber management.
- > Depth: 42cm.

Fiber Capacity		
1.2 meters (22U)	6x 3U Drawer, up to 864 fibers	
2.2 meters (42U)	12x 3U Drawer, up to 1728 fibers	
2.6 meters (58U)	16x 3U Drawer, up to 2304 fibers	



Accessories:

- > Splice & patch drawers: Type HD.
- > Horizontal cable management.
- > Upper duct welded.
- > Vertical high-density cable managements.
- > Bridge connection.
- > Patch cords.

Ordering Information:

FDF-FA___

Unit Height		
12	1.2 meters (22U)	
22	2.2 meters (42U)	
26	2.6 meters (58U)	

Vertical Cable Management		
S	200X251mm	
Т	200x151mm	
G	300x251mm	
None	None	

Example: FDF-FA22G

[Height=42U, Cable Management=300x251mm]

