

GPON POE Wall ONT-4 Ports



Description

GPON Wall ONT is best suited for Passive Optical LAN (POL) network and FTTH residential applications. It provides customers Gigabit Ethernet data along with Power over Ethernet (PoE) services. With POE functionality, it helps to connect any PD terminal device including IP Phone, IP camera, and other equipment. It supports in wall-mounted application, to allow installing the ONT into junction box in the wall.

Specifications

- ✓ ITU G.984.x GPON port with 2.488Gbps (downstream) and 1.244Gbps (upstream)
- ✓ 4x 10/100/1000BASE-T Ethernet Ports
- ✓ PoE on all four ports and LTPoE++ on the first port
- ✓ Power adaptor, BBU and PoE Input Powering Options
- ✓ 0 to 40°C operating temperature

Standards

- ✓ ITU-T G.984.x
- ✓ ITU-T G.984.2 Amendment 1, Class B+
- ✓ ITU-T G.988 OMCI
- ✓ IEEE 802.3 Ethernet LAN
- ✓ IEEE 802.1p/1q VLAN/QoS
- ✓ IEEE 802.3at Types 1 and 2
- ✓ LTPoE++

Performance

General

ONT Type	PoE ONT
Uplink	GPON
Downlinks	4x GE
Operating Temperature	0 to 40°C
Operating Humidity	10% to 90%, non-condensing
Dimensions	121 x 71 x 55mm
Installation	Wall-mount / 118 outlet box
Weight	255g
Regulatory	ETL, CE and FCC

GPON

GPON Interface	1x SC/APC connector, single mode fiber
Standard Compliance	ITU G.984.2 Class B+ Laser safety standard IEC-60825 Class I
Transmitter	1.244Gbps upstream DFB transmitter in 1310nm, with ≥ 10 dB Extinction Ratio Mean launch power in 0.5 to 5dBm range Turn on/off time at burst mode < 12.8 ns
Receiver	2.488Gbps downstream APD receiver in 1490nm, with -8 to -28dBm working range Isolation (1441-1450nm),(1530-1539nm) ≥ 25 dB Isolation (1260-1441nm),(1539-1625nm) ≥ 35 dB
TC Layer	Types 1 to 5 TCONT as defined in G.984.3 32 TCONT, 256 GEM Ports Flexible mapping between TCONT and GEM Ports
GPON Features	Dying Gasp, Forward Error Correction (FEC), Configurable AES decryption in the downstream direction

Ethernet LAN

Ethernet Interface	4 x RJ45 connectors
Standard Compliance	IEEE 802.3, 802.3u, 802.3ab
Link	Half-duplex and full-duplex operations 10/100/1000Mbps auto-negotiation and manual configuration MDI/MDIX auto detection

POE

Standard Compliance	IEEE 802.3at Types 1 and 2, 802.3af, 802.3bt (pre-standard)
Power Output	First port LTPoE++ (max. 60W), all others support max 30W
PSE Channels	four independent PSE Channels
Sense Resistance	0.25Ω sense resistance per channel
Power Device	Automatic detection of Power Type and Status Power Priority Management; support legacy power device and LLDP power device

Layer 2 - Bridging

MAC	Ethernet frame filtering based on port, SA/DA IEEE 802.3as, Max MTU size 2000bytes MAC address limiting
VLAN	IEEE 802.1d bridging Ingress/egress IEEE 802.1p tagging, replacement, and striping IEEE 802.1ad Double tagging Traffic class forwarding to GEMPort and TCONT
QoS	QoS on first 4 ports QoS based on 802.1p and 802.1q 802.1p marking based on DSCP
Multicast	IGMP v2, v3, IGMP snooping

OAM

LED	LED indications and configurable LED hold time
Management	OMCI, CLI, Telnet
Firmware Upgrade	Firmware upgrade, active and alternative firmware images
Diagnostics	Enhanced GPON debug and diagnostic functions Remote debug via telnet from OLT Log files, memory allocation and crash check
Alarm	Alarm report and suppression (ARC)
PM	All standard PM counters

Power

Power Options	DC only
AC-DC Adapter	Phoenix connector 100-240VAC in, 50/60Hz 54VDC out, 1.5A max

Ordering Information

Part Number	Description
FGPON-ONT-W4POE-L	WALL ONT WITH 4 PORTS POE