

Fiber Blocker Secure 4K HDMI Diode

Fibernet's FiberBlocker Diode targets high-level secured environment by separating source and sink data flow while supporting up to 4K resolution. Such separation assures total galvanic isolation between the sink and source sides, including power supplies.

Unidirectional gatekeeping for video data enables information flow from the Source while physically disconnecting traffic from the Sink side.

All Fibernet's Fiber Blocker family are Certified by Israel's Department of Encryption & Cybersecurity



Applications:







Data Centers



Storage Area Networks (SAN)



Communications Rooms

Examples:

- Secure conference rooms
- Secure HDMI monitoring

Features:

- Video and embedded audio transmission quality retained via non-compressed physical layer unidirectional HDMI.
- High-resolution video- up to 4K supported
- Optical and Galvanic separation including separate power supplies
- Auto detect EDID from the monitor device

Configurations:

- 12vDC power supply
- Both input & output HDMI video interface
- Auto detect EDID from the monitor device

Benefits:

- Easy installation
- No software required
- High performance results
- High level of separation between "Sink" and "Source"





Specifications:

| Parameter | Value |
|---------------------------|-------------------------|
| Video Format | HDMI (No HDCP) |
| Resolution | Up to UHD: 2160×3840 |
| Audio Sampling Rate | 96Khz/48Khz/44Khz/32Khz |
| Video Connectors | HDMI 1.4 |
| Optical connectors | SFP+ (any 10G SFP) |
| Input Power Requirements | 12VDC |
| Maximum Power Consumption | 15 Watt |
| Operating Temperature | 0°C ~ +50°C |
| Storage Temperature | -20°C ~ +75°C |
| Operating Humidity | 90% max, non-condensing |
| weight | 450 gr' |
| Dimensions | 165X100X34mm |
| Color | Black |
| Package weight | 850 gr' |
| Package Dimensions | 255x240x80mm |

Ordering Information:

| Part Number | Description |
|-------------|--|
| F-HDMIUSO/2 | FIBERBLOCKER GALVANIC - 4K SECURE HDMI |

Additional Accessories:

| Part Number | Description |
|--------------------|--|
| FIM-5U-SR | 5U SUBRACK FOR EXTENDERS |
| FIM- HDMIUSO/2-ADP | SUBRACK ADPATER FOR 4K SECURE HDMI Diode |

Notes:

^{*}Each extender pair include AC/DC power adapter (2), AC power cable (2), Mounting brackets