

Slim Fiber Optic Distribution Frame 1U



Description:

Fiber-optic distribution frame for termination or distribution of optical fibers. Up to 4 cable entries and Up to 96 fibers in compact size, minimum depth including splice trays

Features:

- > Complies with GR-449-CORE standards.
- > Color - RAL 5009.
- > Large bend radius.
- > Panels for ST, FC, SC, LC.
Other adaptors available according to customer's request

Dimensions:

- > Height: 1U.
- > Depth: 19 cm
- > Width: 19"
Brackets for 21" and 23" should be ordered separately

Accessories:

- > Blank Panels.
- > High quality pigtails.
- > Splice trays for 12 pigtails each.
- > Cable gland for 10–16 mm cables.

Ordering Information:

FPS1 _ _ _ _ _

Adapter Type A		Adapter Type B		Number of Adapters		Splice Trays		Number of Pigtails		Polish Type		Fiber Type	
1	ST Duplex	M	MM	00	None	0	None	00	None	M	None	N	None
2	FC Duplex	S	SM	06	6F	1	12F	12	12F	N	Normal	5	50/125
3	SC simplex	A	APC	12	12F	2	24F	24	24F	P	PC	6	62.5/125
4	SC Duplex	O	OM3	18	18F	3	36F	36	36F	U	UPC	7	G651A2 BI
5	LC Duplex			24	24F	4	48F	48	48F	A	APC	9	9/125
6	LC Quad			36	36F	5	72F	72	72F			O	OM3 BI
				48	48F							G	OM4 BI

Adapter Type A	Number of Adaptors	Number of Pigtails	Splice Tray
ST Duplex	12	24	2
	24	48	4
FC Duplex	12	24	2
	24	48	4
SC Simplex	12	12	1
	24	24	2
SC Duplex	12	24	2
	24	48	4
LC Duplex	12	24	2
	24	48	4
LC Quad	12	48	4
	24	96	N/A